

The examiner has not shown that the claims in each species "ARE PATENTABLE (novel and unobvious) OVER EACH OTHER." Should the requirement for restriction be made final, the examiner is respectfully requested to rule that the claims in each species "ARE PATENTABLE (novel and unobvious) OVER EACH OTHER."

The examiner has made no showing whatsoever that the inventions are INDEPENDENT. M.P.E.P. 803 provides, "If the search and examination of an entire application can be made without serious burden, the examiner must examine it on the merits, even though it includes claims to distinct or independent inventions."

And M.P.E.P. 803.01 provides, "IT STILL REMAINS IMPORTANT FROM THE STANDPOINT OF THE PUBLIC INTEREST THAT NO REQUIREMENTS BE MADE WHICH MIGHT RESULT IN THE ISSUANCE OF TWO PATENTS FOR THE SAME INVENTION."

The main inventive concept of this application is a non-linear (three-dimensional or two-dimensional) ion trap mass spectrometry. Furthermore three other dependent important concepts are: a) switching the ion trap between a three-dimensional mode and a two-dimensional mode by cutting the ring electrode into and operating on the multiple pieces; b) superimpose a DC octopole field on a main quadrupole field by cutting the cap electrodes into and operating on multiple pieces, c) operating the ion trap for ion mass analysis. These concepts work together to provide a complete analysis solution.

Specifically, two further ion trap structures are disclosed implementing abovementioned concepts:

I: A multiple electrodes ion trap which generates a DC octopole field being superimposed on the main RF quadrupole field. When operating as a three-dimensional ion trap, DC octopole field is constructed by cutting two cap electrodes. When operating as two-dimensional ion trap, DC octopole field is constructed by adding a set of small rods electrodes. With disclosed various operating methods and electronics layouts, the mass-ion can be analyzed and mass resolution can be improved, especially, when the ion trap structure and its operating method operate in lower vacuum conditions of 10^{-2} - 10^{-1} mbar.

II: A multiple electrodes ion trap which includes symmetrically cutting, in parallel to its central axis, ring electrodes. This ion trap can generate a three-dimensional ion trap or a two-dimensional multipole ion trap with various disclosed electronics layouts. With disclosed electronics designs, the ion trap can operate and switch in-between a three-dimensional mode and a two-dimensional multipole mode, which improves the ions trapping efficiency.

Species I claims the main inventive concept embedded in structure I in general. Species III claims a three-dimensional ion trap version and mass-analysis method to realize structure I. Species IV claims another three-dimensional ion trap to realize structure I. Species V claims a two-dimensional ion trap version and mass-analysis

method to realize structure I. Species VIII claims the electronics layouts for generating DC octopole field in structure I. Species VII claims a classical ion trap which is operated under lower vacuum condition of 10^{-2} - 10^{-1} mbar.

Species II claims the structure II in general. Species VI claims the specific embodiments to realize structure II. Species IX claims another embodiment to realize structure II.

Manifestly, search and examination of the entire application can be made without serious burden because patents related to the claimed species are coherently connected and related to the same main fundamental inventive concept and its two specific structures implementing the main inventive concept. Accordingly, it is respectfully requested that the requirement for restriction be withdrawn. If the requirement for restriction is repeated, the examiner is respectfully requested to rule that all the different species ARE PATENTABLE (novel and unobvious) OVER EACH OTHER and explain why all the claims cannot be examined without serious burden.

AMENDMENT B

To expedite the process, please amend the application as follows. This listing of claims will replace prior version, and listings, of claims in the application. It will make the amended claim listings to follow the same sole inventive concept:

1. (Currently amended) An ion trap, comprising: a three-dimensional rotationally symmetric ring electrode and two cap electrodes with surfaces facing toward the inside of the ion trap, each said two cap electrodes being further composed of a plurality of component electrodes, ~~the surfaces of said ring electrode and cap electrodes being shaped to reduce nonlinearity~~ a first cone electrode and a second disk electrode; a first means for generating a time-varying, substantially quadrupole field, said means further compensating the nonlinearity induced quadrupole field distortion; means for ions mass analysis, said means utilizing the nonlinearity for providing higher mass resolving power; a second means for generating an independent dipole field; a third means for generating an independent, electrically variable electrostatic multipole field.

2. (Currently amended) An ion trap of claim 65, ~~comprising: a rotationally symmetric ring electrode cut, in parallel to its central axis, into an even number, equal or larger than four, of equal parts and two cap electrodes with surfaces facing toward the inside of the ion trap, said two cap electrode being further composed of a plurality of component electrodes, the surfaces of said ring electrode and cap electrodes being shaped to reduce nonlinearity; means for electrically operating said even number of equal parts to switch said ion trap operation between a three dimensional mode and a two dimensional mode; means for generating a time-varying, substantially quadrupole field, said means further compensating the nonlinearity induced quadrupole field distortion when said ion trap operating under the three dimensional mode; means for generating a linear RF multipole field when said ion trap operating under the two dimensional mode.~~ wherein said ion trap further includes cutting the three-dimensional rotationally symmetric ring electrode, in parallel to its central axis, into an even number, equal or larger than four, of equal parts.

3. (Currently amended) An ion trap of claim 1, ~~comprising: a three-dimensional, rotationally symmetric ring electrode and two cap electrodes with hyperbolic surfaces facing toward the inside of said ion trap, each of said two cap electrodes being further composed of a first hyperbolic cone electrode and a second disk electrode, wherein said first means includes a RF or periodic circuitry constructed and arranged for applying a RF or periodic voltage to said ring electrode to generate a main quadrupole field in said ion trap; said second means includes an AC circuitry constructed and arranged for applying an AC voltage to said disk electrodes of said two cap electrodes to generate a dipole field in said ion trap; said third means includes a DC circuitry constructed and arranged for~~

applying an DC voltage to said cone electrodes of said two cap electrodes to generate an electrically variable electrostatic octopole field in said ion trap.

4. (Currently amended) An ion trap of claim 1, ~~comprising: a three-dimensional, rotationally-symmetric ring electrode and two cap electrodes~~, the surface of each one of the cap electrodes consists of first portion of spherical surface and a second portion of cone surface; the cross-sectional surface of the ring electrode consists of a portion of circle and two straight lines jointed in orthogonal to the circle; the surfaces of the two cap electrodes facing toward the inside of said ion trap.

5. (Original) The ion trap of claim 4 wherein said cap electrodes being further divided into a plurality of sets of component electrodes.

6. (Cancelled)

7. (Currently amended) The ion trap of claim 5 ~~further comprising: wherein~~ said first means includes a RF or periodic circuitry constructed and arranged for applying a RF or periodic voltage to said ring electrode to generate a main quadrupole field in said ion trap; said second means includes an AC circuitry constructed and arranged for applying an AC voltage to a first set of said plurality of sets of component electrodes to generate a main dipole field in said ion trap; said third means includes a DC circuitry constructed and arranged for applying an DC voltage to a second set of said plurality of sets of component electrodes to generate an electrically variable electrostatic octopole field in said ion trap.

8. (Currently amended) A two-dimensional ion trap of claim 67, comprising: two trapping plates located in the two terminals of the ion trap device; a set of four predetermined surface-shaped rods located in the center; a set of electrodes located between the set four predetermined surface-shaped rods; a control circuitry for applying a predetermined voltage to said two trapping plates.

9. (Original) The ion trap of claim 8 further comprising a set of short quadrupole rods located between said predetermined surface-shaped rods and said two trapping plates.

10. (Original) The ion trap of claim 8 wherein said a set of electrodes being further composed of a set of four smaller diameter's cylindrical rods.

11. (Original) The ion trap of claim 8 wherein said a set of electrodes being further composed of a set of four slice electrodes.

12. (Currently amended) The ion trap of claim 8 ~~further comprising: wherein~~ said first means includes a RF circuitry constructed and arranged for applying a RF voltage to said set of four predetermined surface shaped rods to generate a main two dimensional quadrupole field; said second means includes an AC offset

circuitry constructed and arranged for applying an AC voltage to a pair of said set of four predetermined surface shaped rods to generate a main dipole field; said third means includes a DC circuitry constructed and arranged for applying a DC voltage to said set of electrodes to superimposes a two dimensional electrically variable electrodes octopole field within said two dimensional quadrupole field.

13. (Original) The ion trap of claim 8 wherein said predetermined surface-shaped is quadrupole surface-shaped.

14. (Original) The ion trap of claim 8 wherein said predetermined surface-shaped is cylinder surface-shaped.

15. (Original) A tandem mass spectrometers, comprising: a collision cell to perform mass fragment, said collision cell having the structure of ion trap as in claim 8.

16. (Cancelled)

17. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said plurality of even number of component electrodes being equally divided.

18. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said plurality of even number of component electrodes being unequally divided.

19. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said plurality of even number of component electrodes being symmetrically divided.

20. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said plurality of even number of component electrodes being non-symmetrically divided.

21. (Original) The ion trap of claim 17 wherein said even number is chosen from the group of four, six and eight.

22. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said mechanism constructed and arranged to apply a RF or periodic voltage, with identical polarity or phase, to said plurality of even number of component electrodes to operate said ion trap under the three-dimensional quadrupole ion trap mode.

23. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said plurality of even number of component electrodes being grouped into a first set composed of odd numbered component electrodes and a second set composed of even numbered component electrodes, said mechanism constructed and arranged to apply a first RF or periodic voltage to the first set electrodes, and a second RF or periodic voltage to the second set electrodes, to operate said ion trap under the two-dimensional linear ion trap mode; the first and second RF or periodic voltages having opposite polarities or phase deference of 180 degree.

24. (Currently amended) The ion trap of claim ~~16~~ 65 wherein said mechanism being an electrical switching device.

25. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said ion trap operates to trap external inlet ions under the two-dimensional linear ion trap mode.

26. (Currently amended) The ion trap of claim ~~16~~ 2 wherein said ion trap operates to analyze the trapped ion-mass under the three-dimensional quadrupole ion trap mode.

27, 28. (Cancelled)

29. (original) A method of operating an ion trap in claim 3, comprising: keeping amplitude and frequency of the RF voltage or amplitude and period of the periodic voltage at predetermined values; simultaneously sweeping or scanning the amplitude of the DC voltage and the amplitude and frequency of the AC voltage vs. time to eject ion mass from the ion trap one after another.

30. (original) A method of operating an ion trap in claim 7, said method comprising: keeping amplitude and frequency of the RF voltage or amplitude and period of the periodic voltage at predetermined values; simultaneously sweeping or scanning the amplitude of the DC voltage and the amplitude and frequency of the AC voltage vs. time to eject ion mass from the ion trap one after another.

31. (original) A method of operating an ion trap in claim 12, said method comprising: keeping amplitude and frequency of the RF voltage or amplitude and period of the periodic voltage at predetermined values; simultaneously sweeping or scanning the amplitude of the DC voltage and the amplitude and frequency of the AC voltage vs. time to eject ion mass from the ion trap one after another.

32. (Cancelled)

33. (original) A method of operating an ion trap in claim 3, said method comprising: keeping the frequency of the RF voltage or the period of the periodic voltage and the frequency of the AC voltage at predetermined values; Simultaneously sweeping or scanning the amplitudes of the RF voltage or the periodic voltage, the AC voltage and the DC voltage vs the time to eject ion mass from the trap one after another.

34. (original) A method of operating an ion trap in claim 7, said method comprising: keeping the frequency of the RF voltage or the period of the periodic voltage and the frequency of the AC voltage at predetermined values; Simultaneously sweeping or scanning the amplitudes of the RF voltage or the periodic voltage, the AC voltage and the DC voltage vs the time to eject ion mass

from the trap one after another.

35. (original) A method of operating an ion trap in 12, said method comprising: keeping the frequency of the RF voltage or the period of the periodic voltage and the frequency of the AC voltage at predetermined values; Simultaneously sweeping or scanning the amplitudes of the RF voltage or the periodic voltage, the AC voltage and the DC voltage vs the time to eject ion mass from the trap one after another.

36. (Cancelled)

37. (original) A method of operating an ion trap in claim 3, said method comprising: setting the frequency of the AC voltage to zero; setting the amplitude of the AC voltage to be different from the amplitude of the DC voltage or zero; keeping the frequency of the RF voltage or the period of the periodic voltage at predetermined value; Simultaneously sweeping or scanning the amplitudes of the RF voltage and DC voltage vs. time to eject ion mass from the trap one after another.

38. (original) A method of operating an ion trap in claim 7, said method comprising: setting the frequency of the AC voltage to zero; setting the amplitude of the AC voltage to be different from the amplitude of the DC voltage or zero; keeping the frequency of the RF voltage or the period of the periodic voltage at predetermined value; Simultaneously sweeping or scanning the amplitudes of the RF voltage and DC voltage vs. time to eject ion mass from the trap one after another.

39. (original) A method of operating an ion trap in claim 12, said method comprising: setting the frequency of the AC voltage to zero; setting the amplitude of the AC voltage to be different from the amplitude of the DC voltage or zero; keeping the frequency of the RF voltage or the period of the periodic voltage at predetermined value; Simultaneously sweeping or scanning the amplitudes of the RF voltage and DC voltage vs. time to eject ion mass from the trap one after another.

40. (Cancelled)

41. (Original) The ion trap of claim 3 wherein said DC circuitry is controlled to adjust said electrically variable electrostatic octopole field to compensate distortion of said quadrupole field.

42. (Original) The method of claim 29 wherein said ion trap is sealed in a vacuum chamber which is further pumped by a vacuum pump to provide a predetermined level of gas pressure in the trap, the method further adjusts the RF voltage, the DC voltage and the AC voltage along with the gas pressure in the trap

to eject the ions of the ion trap with maximum or near optimal jumping distance to optimize the mass resolving power.

43. (Original) An ion trap system, comprising: an ion trap as in claim 3, sealed within a vacuum chamber being pumped by a vacuum pump to provide gas pressure in the ion trap.

44. (Original) An ion trap system, comprising: an ion trap as in claim 7, sealed within a vacuum chamber being pumped by a vacuum pump to provide gas pressure in the ion trap.

45. (Original) An ion trap system, comprising: an ion trap as in claim 12, sealed within a vacuum chamber being pumped by a vacuum pump to provide gas pressure in the ion trap.

46. (Cancelled)

47. (Original) The ion trap system of claim 43 wherein said vacuum chamber having vacuum in the range between 10^{-2} to 10^{-1} mbar.

48. (Original) The ion trap system of claim 43 wherein said DC circuitry being constructed and arranged for applying an DC voltage to adjust the intensity of said electrically variable electrostatic octopole field in said ion trap to optimize the mass resolving power when said gas pressure is higher.

49. (Original) A method for providing ions into ion trap system of claim 43, comprising: introducing gas-phase molecules through a membrane into an ionization area; ionizing said gas-phase molecules by a radioactive Ni beta source or multi-photon ionization of laser.

50. (Original) The ion trap system of claim 44 wherein said vacuum chamber having vacuum in the range between 10^{-2} to 10^{-1} mbar.

51. (Original) The ion trap system of claim 44 wherein said DC circuitry being constructed and arranged for applying an DC voltage to adjust the intensity of said electrically variable electrostatic octopole field in said ion trap to optimize the mass resolving power when said gas pressure is higher.

52. (Original) A method for providing ions into ion trap system of claim 44, comprising: introducing gas-phase molecules through a membrane into an ionization area; ionizing said gas-phase molecules by a radioactive Ni beta source or multi-photon ionization of laser.

53. (Original) The ion trap system of claim 45 wherein said vacuum chamber having vacuum in the range between 10^{-2} to 10^{-1} mbar.

54. (Original) The ion trap system of claim 45 wherein said DC circuitry being constructed and arranged for applying an DC voltage to adjust the intensity of said electrically variable electrostatic octopole field in said ion trap to optimize the mass resolving power when said gas pressure is higher.
55. (Original) A method for providing ions into ion trap system of claim 45, comprising: introducing gas-phase molecules through a membrane into an ionization area; ionizing said gas-phase molecules by a radioactive Ni beta source or multi-photon ionization of laser.
56. (Cancelled)
57. (Cancelled)
58. (Cancelled)
59. (Original) An ion trap system, comprising: A three-dimensional ion trap, said ion trap being sealed within a vacuum chamber, said vacuum chamber has vacuum in the range between 10^{-2} to 10^{-1} mbar.
60. (Original) The ion trap system of claim 59 wherein said three-dimensional ion trap is a Paul trap.
61. (Original) A three-dimensional ion trap, comprising: A set of cap electrodes, each of said cap electrodes being further divided into a predetermined number of component electrodes having predetermined shape, a DC circuitry constructed and arranged for applying an DC voltage to a pair of said component electrodes of said cap electrodes to generate an independent electrically variable electrostatic octopole field in said ion trap.
62. (Original) An ion trap, comprising: a ring electrode, the ring electrode being divided, in parallel to its central axis, into a plurality of even number of component electrodes, said component electrodes being electrically isolated from each other; a mechanism constructed and arranged for switching said ion trap to operate between a three-dimensional quadrupole ion trap mode and a two-dimensional linear ion trap mode.
63. (Original) The ion trap of claim 62 wherein said ring electrode is a cylindrical ring electrode.
64. (New) The ion trap of claim 1 wherein said ion trap further includes operating means for ions mass analysis, said means utilizing the independent, electrically variable electrostatic multipole filed.

65. (New) The ion trap of claim 1 wherein said ion trap further includes a mechanism for electrically switch said ion trap to operate between a three-dimensional mode and a two-dimensional mode.

66. (New) An ion trap of claim 2, said means for electrically switch includes operating said even number of equal parts to switch said ion trap operation between a three-dimensional mode and a two-dimensional mode and wherein said ion trap further includes means for generating a linear RF multipole field when said ion trap operating under the two-dimensional mode.

67. (New) A two-dimensional ion trap, comprising: a first means for generating a time-varying, two-dimensional substantially quadrupole field, a second means for generating an independent dipole field; a third means for superimposing an independent, two-dimensional electrically variable electrostatic multipole field.